



## Special products

Product information  
MR<sup>®</sup> 200 Teflon-Spray

**MR**<sup>®</sup>  
CHEMIE  
NDT-materials

TO SEE MORE!

## MR<sup>®</sup> 200 Teflon\*-Spray

for universal application possibilities

---

### General description:

- mixture of solvents containing special agents
- dries quickly
- is outstanding for its non-adhesive characteristics and very low coefficients of friction
- provides a fat-free dry lubrication
- prevents the adhesion of fat, water, paint and dirt
- suitable for metal or plastic surfaces
- heat-resistant up to approx. + 250 °C and cold-resistant up to - 200 °C

### Application:

- derust surface thoroughly and degrease with e.g. MR<sup>®</sup> 79 Special cleaner; shake aerosol well; application at room temperature and good ventilation.
- apply a thin film on the surface. To achieve a thicker film, apply a thin film, allow to dry, polish surface and repeat the steps until the film has the desired thickness

### Minimum shelf life:

- will keep for a minimum of 4 years, stored at room temperature

### Pack sizes:

- aerosols, 500 ml (1 box contains 12 aerosols)

\* Trademark of Du Pont

11.03.2015/db

\*\*Technical changes reserved!\*\*

NDT-materials

CRACK

Marker