

MR[®] 312 Penetrant red and fluorescent



Product Characteristics

- Water and solvent removable penetrant red and fluorescent
- Penetrant Typ III
- Sensitivity level 2 acc. EN ISO3452
- Crack indication colour „red and fluorescent“
- Suitable for all metals with excellent wetting properties (suitability for plastics and ceramics must be checked before use)
- Carrier medium Alcohol

Minimum shelf life / Temperatures

Aerosol / Bulk: 3 years at storage
temperature
Storage: + 5 °C - + 45 °C
Application: - 30 °C - + 50 °C



Approvals / Specification



- EN ISO 3452-2
- EN ISO 3452-6
- ASTM E165
- RCC-M
- ASME Code V, Art. 6
- VDA236-150

Further Information

Process description according to EN ISO 3452-1 on request or on www.mr-chemie.de/en. For further information see Material Safety Data Sheet and certificate 3.1. For additional equipment please visit our Homepage or contact our sales team.

The minimum order quantity for bulk containers is: 30 litres

Suggested Products

Pre-cleaner: MR[®] 79, MR[®] 85, MR[®] 88
Remover: MR[®] 79, MR[®] 85, MR[®] 88
Developer: MR[®] 70
Test blocks Reference-Testblock 1 and 2, ASTM Testblock

Delivery Form



technical changes reserved!