

MR[®] 62 AMS Penetrant red



Product characteristics

- Water washable penetrant red
- Penetrant type 2 according to ASTM E1417
- Listed in QPL SAE AMS 2644
- Sensitivity class 2 according to AMS 2644
- Crack indication colour red
- Suitable for all metals (suitability for plastics and ceramics to be checked before application)
- Carrier medium: mineral oil

Minimum shelf life / temperatures

Aerosole / Bulk:
3 years at storage temperature
Storage: + 5 °C - + 45 °C
Application: + 4 °C - + 52 °C



Approvals / Specification



- ASME B & PV Code, Sec V
- ASTM E1135
- QPL SAE AMS 2644
- ASTM E1417
- ASTM E165
- ASME Code V Art. 6
- ASME
- RCC-M

Further information

Process description according to ASTM E1417 on request or on www.mr-chemie.de/en. For further information see Material Safety Data Sheet and certificate 3.1. For additional equipment please visit our Homepage or contact our sales team.

Suggested products

Pre-cleaner: MR[®] 79, MR[®] 85, MR[®] 88, MR[®] 3001, MR[®] 3002
Remover: MR[®] 88, MR[®] 79
Developer: MR[®] 70 I
Test body: Reference test block 1, Reference test block 2, Test block

Delivery form



Technical changes reserved!