

**MR<sup>®</sup> 703 W Developer white**



**Product Characteristics**

- Developer for penetrant type I, II & III
- Carrier medium Water
- Very easy removable from the surface

**Minimum shelf life /  
Temperatures**

2 years at storage temperature  
Storage: + 5 °C - + 45 °C  
Application: + 5 °C - + 100 °C



**Approvals /  
Specification**

- EN ISO 3452-2
- EN ISO 3452-5
- ASME Code V, Art. 6
- VDA236-150
- ASTM E165
- ASTM D516
- RCC-M



**Further Information**

Process description according to EN ISO 3452-1 on request or on [www.mr-chemie.de/en](http://www.mr-chemie.de/en). For further information see Material Safety Data Sheet and certificate 3.1. For additional equipment please visit our Homepage or contact our sales team.

**Suggested Products**

Pre-cleaner: MR<sup>®</sup> 71, MR<sup>®</sup> 79, MR<sup>®</sup> 85, MR<sup>®</sup> 88, MR<sup>®</sup> 3001, MR<sup>®</sup> 3002  
Remover: MR<sup>®</sup> 79, MR<sup>®</sup> 85, MR<sup>®</sup> 88, Water  
Penetrant: All penetrants type I, II & III; not for System "HOT" and AMS  
Test block: Reference-Testblock 1, Reference-Testblock 2 und ASTM Testblock  
Equipment PN 2A, M-Air-Electronic

**Delivery Form**



\*\*Technical changes reserved!\*\*