

# PRODUCT INFORMATION

## Penetrant Testing



### MR® 85 Remover



#### Product characteristics

- Pre-cleaner and penetrant remover
- Colourless
- Suitable for all metals and ceramics (suitability for plastics must be checked before use)
- Carrier medium Alcohol

#### Minimum shelf life / Temperatures

Aerosol / Bulk:

3 years at storage temperature

Storage: + 5 °C - + 45 °C

Application: - 10 °C - + 50 °C



#### Approvals / Specifications

- EN ISO 3452-2
- EN ISO 3452-6
- ASTM E165
- ASME Code V, Art. 6
- PMUC
- RCC-M
- TLV 9017 01:2011-01
- VDA236-150

#### Further information

Process description according to EN ISO 3452-1 on request or on [www.mr-chemie.de/en](http://www.mr-chemie.de/en). For further information see Material Safety Data Sheet and certificate 3.1. For additional equipment please visit our Homepage or contact our sales team.

#### Suggested products

Penetrant: For all penetrant typ I, II and III; not for System "HOT"

Developer: MR® 70, MR® 70 I (AMS), MR® 703 W (+5 °C)

Test block: Reference-Testblock 1 and 2, ASTM Testblock

#### Delivery form



\*\*Technical changes reserved!\*\*