

MR[®] 703 WK Developer Concentrate

PRODUCT CHARACTERISTICS

- Developer for penetrant testing acc. to EN ISO 3452:2 Type I, II and III
- Carrier medium Water
- Very easy suspendability
- Dilute MR[®] 703 WK Developer Concentrate 5% -10% with water
- Easy removability from the surface

APPROVALS / SPECIFICATION

Data refer to the ready-to-use solution:

- | | | |
|-----------------------|-------------|---------|
| ▪ EN ISO 3452-2 | ▪ ASTM E165 | ▪ RCC-M |
| ▪ EN ISO 3452-5 | ▪ ASTM D516 | |
| ▪ ASME Code V, Art. 6 | | |

SUGGESTED PRODUCTS

Approvals / Conformities acc. DIN EN ISO 3452-2:

Pre-cleaner:	MR [®] 79, MR [®] 85, MR [®] 88, MR [®] 3001 und MR [®] 3002
Remover:	MR [®] 79, MR [®] 85, MR [®] 88, Water
Penetrant:	For all penetrant type I, II and III; not for System "HOT" and AMS approved products)
Test block's:	Reference-Testblock 1, Reference-Testblock 2 und ASTM Testblock

MINIMUM SHELF LIFE / TEMPERATURES

Aerosol/Bulk: 3 years at ambient storage temperature

Storage: +5 °C - +45 °C

Application: +5 °C - +100 °C

DELIVERY FORM



FURTHER INFORMATION

- Process description according to **EN ISO 3452-1** on request or on www.mr-chemie.de/en.
- For further information see Material Safety Data Sheet and certificate 3.1.
- For additional equipment please visit our Homepage or contact our sales team.