

MR[®] 70 Developer

PRODUCT CHARACTERISTICS

- Developer for penetrant testing acc. to EN ISO 3452:2
- Carrier medium Solvent
- Very easy removable from the surface

APPROVALS / SPECIFICATION

- | | | |
|-----------------------|-----------------------|--------------|
| • EN ISO 3452-2 | • ASTM E165 | • RCC-M |
| • EN ISO 3452-6 | • ASTM E1417 | • PMUC |
| • ASME Code V, Art. 6 | • TLV 9017 01:2011-01 | • JIS 2343-2 |

SUGGESTED PRODUCTS

Approvals / Conformities acc. DIN EN ISO 3452-2:

Pre-cleaner: MR[®] 79, MR[®] 85, MR[®] 88, MR[®] 3001 und MR[®] 3002
Remover: MR[®] 79, MR[®] 85, MR[®] 88, Water
Penetrant: For all penetrant typ I, II and III; not for System "HOT" and AMS approved products)
Test block's: Reference-Testblock 1, Reference-Testblock 2 und ASTM Testblock

MINIMUM SHELF LIFE / TEMPERATURES

Aerosol/Bulk: 3 years at ambient storage temperature

Storage: +5 °C - +45 °C
Application: -10 °C - +50 °C
Application: -30°C - +50 °C (with MR[®] 312, MR[®] 79, MR[®] 85 or MR[®] 88)

DELIVERY FORM



FURTHER INFORMATION

- Process description according to **EN ISO 3452-1** on request or on www.mr-chemie.de/en.
- For further information see Material Safety Data Sheet and certificate 3.1.
- For additional equipment please visit our Homepage or contact our sales team.