

MR® 81 Food Safe Dry Developer

PRODUCT CHARACTERISTICS

- Developer powder for penetrant testing
- Suitable for the food industry (additionally MR® 955)
- Easy removability

APPROVALS / SPECIFICATION

- | | | |
|-----------------|-------------|-----------------------|
| ▪ EN ISO 3452-2 | ▪ ASTM E165 | ▪ RCC-M |
| ▪ ASTM E1417 | ▪ NSF | ▪ ASME Code V, Art. 6 |

SUGGESTED PRODUCTS

Approval according to EN ISO 3452-2:

Cleaner: MR® 71, MR® 79, MR® 85, MR® 88, MR® 3001 and MR® 3002
Penetrant: for all penetrants of type I
Remover: MR® 79, MR® 85, MR® 88, water
Test block: Reference block type 1, Reference block type 2 and ASTM test block

MINIMUM SHELF LIFE / TEMPERATURES

Aerosol/bulk: 3 years, at storage temperature

Storage: +5 - +45 °C

Application: +10 - +50 °C

DELIVERY FORM

- 1 kg (10 L plastic bucket)
- 100g (1,1 L plastic can)

FURTHER INFORMATION

- Process description according to **EN ISO 3452-1** on request or on www.mr-chemie.de/en.
- For further information see Material Safety Data Sheet and certificate 3.1.
- For additional equipment please visit our Homepage or contact our sales team.