

### MR<sup>®</sup> 88 Remover AMS 2644 – Class 2 - Solvent

#### PRODUCT CHARACTERISTICS

- Pre-cleaner and penetrant remover
- Colourless
- Slowly drying
- Suitable for all metals and ceramics (suitability for plastics must be checked before use)
- Carrier medium Alcohol

#### APPROVALS / SPECIFICATION

- EN ISO 3452-2
- EN ISO 3452-6
- AMS 2644
- ASTM E165
- ASME Code V, Art. 6
- ASTM E1417
- RCC-M
- TLV 9017 01:2011-01

#### SUGGESTED PRODUCTS

##### Approvals / Conformities acc. DIN EN ISO 3452-2:

Penetrant: For all penetrant typ I, II and III; not for System "HOT"  
Developer: MR<sup>®</sup> 70, MR<sup>®</sup> 70 I (AMS), MR<sup>®</sup> 703 W (+5 °C)  
Test block's: Reference-Testblock 1, Reference-Testblock 2 und ASTM Testblock

#### MINIMUM SHELF LIFE / TEMPERATURES

Aerosol/Bulk: 3 years at ambient storage temperature

Storage: +5 °C - +45 °C

Application: -30 °C - +52 °C

#### DELIVERY FORM



#### FURTHER INFORMATION

- Process description according to **EN ISO 3452-1** on request or on [www.mr-chemie.de/en](http://www.mr-chemie.de/en).
- For further information see Material Safety Data Sheet and certificate 3.1.
- For additional equipment please visit our Homepage or contact our sales team.