

### MR<sup>®</sup> 91 H Remover

#### PRODUCT CHARACTERISTICS

- Pre-cleaner and Penetrant remover for high temperature application between +50°C and +200°C
- Fast drying
- Colourless
- Suitable for all metals and ceramics
- Carrier medium Hydrocarbons

#### APPROVALS / SPECIFICATION

- EN ISO 3452-2
- EN ISO 3452-5
- ASTM E165
- ASME Code V, Art. 6
- RCC-M

#### SUGGESTED PRODUCTS

##### Approvals / Conformities acc. DIN EN ISO 3452-2:

Penetrant: MR<sup>®</sup> 68 H  
Developer: MR<sup>®</sup> 70 H  
Test block's: Reference-Testblock 1, Reference-Testblock 2 und ASTM Testblock

#### MINIMUM SHELF LIFE / TEMPERATURES

Aerosol/Bulk: 3 years at ambient storage temperature

Storage: +5 °C - +45 °C  
Application: +50 °C - +200 °C

#### DELIVERY FORM



#### FURTHER INFORMATION

- Process description according to **EN ISO 3452-1** on request or on [www.mr-chemie.de/en](http://www.mr-chemie.de/en).
- For further information see Material Safety Data Sheet and certificate 3.1.
- For additional equipment please visit our Homepage or contact our sales team.