

## MR<sup>®</sup> 670 F Piccolo-Pen

### Product Characteristics

- Water washable penetrant fluorescent
- Penetrant Type I
- Sensitivity level 0.5 acc. EN ISO3452
- Crack indication colour yellow and yellow fluorescent
- Suitable for all metals (suitability for plastics and ceramics must be checked before use)
- Carrier medium Glycol



### Minimum shelf life / Temperatures

3 years at storage temperature  
Storage: + 5 °C - + 45 °C  
Application: - 10 °C - + 50 °C



### Approvals / Specification

- EN ISO 3452-2
- ASME Code V, Art. 6
- ASTM E165
- RCC-M
- PMUC
- VDA236-150



### Further Information

Process description according to EN ISO 3452-1 on request or on [www.mr-chemie.de/en](http://www.mr-chemie.de/en). For further information see Material Safety Data Sheet and certificate 3.1. For additional equipment please visit our Homepage or contact our sales team.

### Suggested Products

Pre-cleaner: MR<sup>®</sup> 79, MR<sup>®</sup> 85, MR<sup>®</sup> 88, MR<sup>®</sup> 3001, MR<sup>®</sup> 3002  
Remover: Water  
Developer: MR<sup>®</sup> 70, MR<sup>®</sup> 703 W (+5 °C), MR<sup>®</sup> 81 T-R  
Test block: Reference-Testblock 1 and 2, ASTM Testblock

### Delivery Form



\*\*Technical changes reserved!\*\*