

MR[®] 672 F Piccolo-Pen

Product Characteristics



- Water washable penetrant fluorescent
- Penetrant Type I
- Sensitivity level 2 acc. EN ISO 3452
- Crack indication colour yellow and yellow fluorescent
- Suitable for all metals (suitability for plastics and ceramics must be checked before use)
- Carrier medium Glycol, Ester

Minimum shelf life / Temperatures

Aerosol / Bulk:
3 years at storage temperature
Storage: + 5 °C - + 45 °C
Application: + 10 °C - + 50 °C



Approvals / Specification

- EN ISO 3452-2
- ASME Code V, Art. 6
- VDA236-150




Further Information

Process description according to EN ISO 3452-1 on request or on www.mr-chemie.de/en. For further information see Material Safety Data Sheet and certificate 3.1. For additional equipment please visit our Homepage or contact our sales team.

Suggested Products

Pre-cleaner: MR[®] 79, MR[®] 85, MR[®] 88, MR[®] 3001, MR[®] 3002
Remover: Water
Developer: MR[®] 70, MR[®] 703 W (+5 °C), MR[®] 81 T-R
Test block: Reference test block 1 & 2 and ASTM test block
UV light: MR[®] 975, MR[®] 96 E, MR[®] 96 ESL

Delivery Form



technical changes reserved!