

MR[®] 67 Penetrant red and fluorescent



Product Characteristics

- Water and solvent removable penetrant red and fluorescent
- Penetrant Typ II and Typ III
- Sensitivity level 2 acc. EN ISO 3452
- Crack indication colour „red and fluorescent“
- Suitable for all metals (suitability for plastics and ceramics to be checked before application)
- Carrier medium water

Minimum shelf life / Temperatures

Aerosol / Bulk:
3 years at storage temperature
MR® 67 DL: 1 year at storage temperature
Storage: + 5 °C - + 45 °C
Application: + 5 °C - + 100 °C
MR® 67 PS + 5 °C - + 50 °C



Approvals / Specification

- EN ISO 3452-2
- EN ISO 3452-5
- ASTM D516
- ASTM E165
- RCC-M
- ASTM E1417
- ASME Code V, Art. 6
- VDA236-150



Further Information

Process description according to EN ISO 3452-1 on request or on www.mr-chemie.de/en. For further information see Material Safety Data Sheet and certificate 3.1. For additional equipment please visit our Homepage or contact our sales team.

Suggested Products

Pre-cleaner: MR® 79, MR® 85, MR® 88, MR® 3001, MR® 3002
Remover: MR® 79, MR® 85, MR® 88, Water
Developer: MR® 70, MR® 703 W (+5 °C)
Testblock: Reference-Testblock 1 and 2, ASTM Testblock

Delivery Form



technical changes reserved!