

MR[®] 68 C Piccolo-Pen

Product Characteristics



- Water and solvent washable penetrant red and fluorescent
- Penetrant type II and type III
- Sensitivity class 2 according to EN ISO 3452
- Crack indicator red and (UV) red fluorescent
- Suitable for all metals, ceramics and very good wetting properties on smooth and polished surfaces
- Carrier medium mineral oil and glycol

Minimum shelf life / Temperatures

Aerosol / Bulk:
3 years at storage temperature
Storage: + 5 °C - + 45 °C
Application: - 10 °C - + 50 °C



Approvals / Specification

- EN ISO 3452-2
- EN ISO 3452-6
- ASTM E165
- ASME Code V, Art. 6
- VDA236-150
- RCC-M
- PMUC
- TLV 9017
01:2011-01




Further Information

Process description according to EN ISO 3452-1 on request or on www.mr-chemie.de/en. For further information see Material Safety Data Sheet and certificate 3.1. For additional equipment please visit our Homepage or contact our sales team.

Suggested Products

Pre-cleaner: MR[®] 79, MR[®] 85, MR[®] 88, MR[®] 3001, MR[®] 3002
Remover: MR[®] 79, MR[®] 85, MR[®] 88, Wasser
Developer: MR[®] 70, MR[®] 703 W (+5 °C)
Test block: Reference-Testblock 1 and 2, ASTM Testblock

Delivery Form



technical changes reserved!