

MR[®] 703 WK Developer white concentrate



Product Characteristics

- Water-suspendable developer concentrate for penetrant testing type I, II and III
- Good suspendability
- Carrier medium water
- Easy removability

**Minimum shelf life /
Temperatures**

2 years at storage temperature
Storage: + 5 °C - + 45 °C
Application: + 5 °C - + 100 °C



**Approvals /
Specification**

- EN ISO 3452-2
- EN ISO 3452-5
- ASME Code V, Art. 6
- VDA236-150
- ASTM E165
- ASTM D516
- RCC-M



Further Information

Process description according to EN ISO 3452-1 on request or on www.mr-chemie.de/en. For further information see Material Safety Data Sheet and certificate 3.1. For additional equipment please visit our Homepage or contact our sales team.

Suggested Products

Pre-cleaner: MR[®] 71, MR[®] 79, MR[®] 85, MR[®] 88, MR[®] 3001, MR[®] 3002
Remover: MR[®] 79, MR[®] 85, MR[®] 88, Water
Penetrant: All penetrants type I, II & III; not for System "HOT" and AMS
Test block: Reference-Testblock 1, Reference-Testblock 2 und ASTM Testblock
Equipment PN 2A, M-Air-Electronic

Delivery Form



Technical changes reserved!