




MR[®] 756 Coupling agent powder



Product Characteristics

- Coupling gel powder for mixing to ready-to-use gel with water
- 125 g for 5 liters of ready-to-use coupling gel, equivalent to 1:40
- Non-toxic, non-flammable
- Formaldehyde-free
- High viscosity, non-drip
- Good conductivity
- Excellent for air displacement between the ultrasonic probe and the surface to be tested
- ECO-LINE

Minimum shelf life / Temperatures

Powder: 2 years at storage
temperature (unopened)
Storage: + 5 °C - + 45 °C
Application: + 10 °C - + 85 °C



Approvals / Specification

- DIN EN ISO 25493



Application

1. Mix MR[®] 756 to ready-to-use gel after instruction.
2. Apply to the material, place the test head on it and start the test. MR[®] 756 spreads evenly under the test head.
3. MR[®] 756 can also be used for coated materials, plastics, rubber/metal joints, etc. However, we recommend that tests be carried out in advance.
4. MR[®] 756 coupling gel can be easily removed after testing.
5. For materials that are very susceptible to rust (e.g. gray cast iron, etc.), we recommend the addition of MR[®] 302 Rust Protection Concentrate.

Further information

Further information is available on request or at www.mr-chemie.de/en as well as in our safety data sheet and our 3.1 certificate.

Delivery form



Technical changes reserved!