

MR[®]955-1 Fluorescent Food Area Penetrant



Product Characteristics

- Water washable fluorescent penetrant
- Penetrant Typ I
- Sensitivity level 1 acc. EN ISO 3452
- Crack indication yellow fluorescent (UV)
- Suitable for all metals (suitability for plastics and ceramics must be checked before use)
- Carrier medium alcohol



Nonfood Compounds
H2

Minimum shelf life / Temperatures

Bulk:
3 years at storage temperature
Storage: + 5 °C - + 45 °C
Application: + 10 °C - + 50 °C



Approvals / Specification

- EN ISO 3452-2
- ASME Code V, Art. 6
- RCC-M
- NSF[®] Code H2



Further Information

Process description according to EN ISO 3452-1 on request or on www.mr-chemie.de/en. For further information see Material Safety Data Sheet and certificate 3.1. For additional equipment please visit our Homepage or contact our sales team.

MPA test according to EN ISO 3452-2 was passed => sensitivity level 1 without developer (self-assessment)

Suggested Products

Pre-cleaner: MR[®] 71, MR[®] 79, MR[®] 85, MR[®] 88, MR[®] 3002
Remover: Water
Developer: MR[®] 81 Food safe dry developer
Test blocks: Reference test block 1 and 2, ASTM test block

Delivery Form



Technical changes reserved!