



MR[®] 96 ESL UV LED Flashlight with Spray Aid



Product Characteristics

- UV LED flashlight with ergonomic spray aid (**Art. 4763**)
- White light <5 lux thanks to to MUG filter
- Enables fatigue-free spraying
- Easy application and controlled dosage
- One year warranty incl. UV LED
- Compatible with 96 DSL spray aid
- Certificate is supplied

Technical Data

Item number	96E (Art. 4763)
UV lamp risk class acc. to DGZfP EM6*	3
UVA*	Max. 30 Watt/m ²
Cone of light	Ø 140mm > 10 Watt/m ²
Weight without battery	64 g
Dimensions	L = 120 mm, Ø = 24 mm
Wavelength (Peak)	365 nm ± 5 nm
Power supply	1x 18650 Lithium
Operating time	Depending on the battery, min. 1.5 hrs.
Lifespan UV LED**	ca. 10,000 h
Waste heat	45 °C
IP protection class acc. to DIN EN 60529	IP67 (waterproof)

*measured at a distance of 38 cm from the surface

**under laboratory conditions according to the manufacturer's instructions



Technical changes reserved!




MR[®] 96 ESL UV LED Flashlight with Spray Aid

Scope of Delivery



MR 96 E
UV LED flashlight

Art. 4762



CASE
Suitable for MR 96 E

Art. 162



2 LITHIUM-ION BATTERIES
Type 18650



USB CHARGER
For Battery Type 18650



SPRAY AID
Ergonomic

Art. 118

Optionally available



CHARGER
Forr 2x Li-Ion Battery
(Charging time 4 hrs.)

Art. 211



2 X 18650 ERSATZ-AKKUS **Art. 264**
Suitable for MR 96 E



****Technical changes reserved!****